



STYLE BETON

Color Hardener

<p>DESCRIPTION</p>	<p>The STYLE BETON COLOR HARDENER is ready to use product, dry, fine particle size distribution of quartz. Integrates easily into the surface of fresh concrete. The Style Beton Color Hardener penetrates the surface of the concrete increases the resistance of everyday wear, to temperature changes, acid and salts. Available in bags of 25 kg, is ready for use in a variety of 27 colours.</p> <p>The Style Beton Color Hardener is composed of inert quartz, high-quality colour Bayer, silica, high-quality Portland cement type I, iron oxides and other additional hardener. .</p>
<p>Colors</p> <p>Restrictions</p> <p>Packaging</p> <p>Storage</p>	<p>Available in 27 colors.</p> <p>Do not apply the product of the likelihood of rain, the temperature of the substrate below 5 ° C and above 30 ° Celsius.</p> <p>25 kg</p> <p>At room temperature onto pallets. Protect from moisture.</p>
<p>Application</p>	<p>Spread the Style Color Hardener in fresh concrete surface in two layers. The first layer should be rich, 1.5kg/tm. Leave time Style Color Hardener to get wet and be fully integrated. Then spread with a special spatula. It is recommended the second layer to be spread in smaller quantity, 1 kg / m², and follow exactly the same procedure. In floors, intended for heavy use</p>

	(roads, parking areas, ramps), the total quantity of Style Color Hardener exceed 4kg/tm.
CLEANING	The tools are recommended to be cleaned immediately after use with water.
HEALTH AND SAFETY	Read the label before use .During the preparation of surfaces avoid the inhalation of dust. Use a face mask and gloves. It contains toxic.
GENERAL INFORMATION	<p>Note that the technical application and the experience of work teams will affect the final aesthetic result of the floor.</p> <p>The information and in particular the recommendations relating to the application and final use of products «STYLE BETON» given in good faith, based on current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual application conditions are such that no guarantee can be given in respect of merchantability or fitness for a particular purpose and no liability of any legal relationship can be established against the company based here in labeling information, written recommendations, or other advice offered. Respect the rights of others is essential. Users must always refer to the most recent version of this.</p> <div data-bbox="858 1243 1023 1422" data-label="Image"> </div> <p style="text-align: center;">STYLE BETON</p> <p style="text-align: center;">Navarinou 8, Kalochori, Thessaloniki, Greece, 57009 TEL. : 0030 2310 - 920831, FAX : 0030 2310 - 920832, www.stylebeton.com , info@stylebeton.com</p>