



STYLE BETON®

Industrial Flooring

Description	<p>The Style Industrial is a chemical hardener in powder form, consisting of cement, quartz grain size and varying colors of German origin. Available in 27 colors ready to use.</p> <p>Creates industrial, colored, smooth floors high resistance to abrasion and mechanical stress, while using the helicopter for proper integration into the fresh concrete (minimum concrete quality: C16/20).</p> <p>Ideal for flooring industries, garages, warehouses, parking, units of food for the surrounding areas, walkways, ramps and floors generally for medium and heavy traffic.</p> <p>Suitable for application to external and internal surfaces.</p>
Colors	<p>Available in 27 colors.</p>
Restrictions	<p>Do not apply in case of rain. The application temperature of the material should be 5-35 ° C.</p>
Packaging	<p>25 kg</p>
Storage	<p>At room temperature, onto pallets. Protect from moisture.</p>
Application	<p>The Style Industrial can be applied dry and sprinkled on the fresh concrete or cement screed, as they start to be coagulated but before final coagulation. Then the material is worked with a special grinding machine (helicopter) or special spatula to incorporate properly the fresh concrete. After seven (7) days and after reaching the 80% hardness, apply special sealer Style Sealer and cut joints expansion - systole every 25m².</p>
Consumption	<p>2,5-4kg / m² depending on the function of the floor and the color we choose.</p>
Safety Instructions	<p>The application must be in well ventilated areas with protective gloves. When the material comes into contact with the skin should be washed thoroughly with soap and water.</p>
General Information	<p>Note that application procedures and experience of the workshops will affect the final aesthetic result of the floor.</p>

The information and in particular the recommendations relating to the use and final product application «STYLE BETON ®» given in good faith, based on current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and the realities are such that there is no guarantee can be given in respect of merchantability or fitness for a particular purpose and is not liable for any legal relationship can be demonstrated to the company based here in labeling information, or from any other advice offered. Users should always refer to the most recent version of this.



STYLE BETON®

Navarinou 8, Kalochori, Thessaloniki, Greece, 57009
TEL. : 0030 2310 - 920831, FAX : 0030 2310 - 920832,
www.stylebeton.com , info@stylebeton.com