



STYLE SEALER

100% clear acrylic sealer of 1 ingredient.

DESCRIPTION	<p>100% high quality acrylic sealer for all internal and external use. The main product features are:</p> <ul style="list-style-type: none"> • Excellent mechanical and chemical resistance • Easy application with excellent spreading • Crystal-clear, transparent film final • Velvet surface • Strong adhesion and fast drying • Resistance to weather and UV radiation • Easy to clean <p>The STYLE SEALER not ever yellowing. It has a large measure of flexibility and will not peel off. Decorate and protect surfaces such as slates, ceramic tiles, decorative bricks, porous stone, tiles, marble, stone constructions, stamped concrete, etc.</p>
Density	0,90 gr/ml
Flashpoint	40 °C
VOC content	730 gr/lt
Toxicity	Contains xylene. Consult Product Material Safety Data Sheet for proper use. It does not contain lead.
pH	8.9
Shade	Available in transparent.
Restrictions	Do not apply the product of the likelihood of rain, strong wind, the temperature of the substrate below 8 ° C and if the relative humidity exceeds 80% by the use or drying.
Packaging	20lt
Storage	At room temperature. Protect from freezing.

<p>SUBSTRATE PREPARATION</p> <p>New surfaces</p> <p>Painted surfaces</p>	<p>All surfaces must be dry and clean, free from dust, oil, grease, wax, rust, salt, mould, loose parts and generally anything that prevents the adhesion of materials to be used. The STYLE SEALER applied in 2 coats depending on the desired sheen.</p> <p>All surfaces must be dry and clean, free from dust, oil, grease, wax, rust, salt, mould, loose parts and generally anything that prevents the adhesion of materials to be used. Old varnish have lost grip completely removed. Mould can be removed with liquid against mould under the manufacturer's instructions. Surface imperfections (holes, tears, etc.) repaired with an appropriate grout. Coatings stone water with a strong grip scrub gently until done mate. Remove dust. We apply 2 coats STYLE SEALER depending on the desired sheen.</p>
<p>APPLICATION</p>	<p>Stir well before and during application. The STYLE SEALER is ready for use. Proposed to use a brush with a uniform thickness. Synthetic brush with soft, thin, long hair gives the best results. In large surfaces apply with a short hair roller. Proposed 2 layers for greater protection and stunning shine.</p>
<p>CLEANING</p>	<p>. The tools are cleaned immediately after application with STYLE SOLVENT</p>
<p>HEALTH AND SAFETY</p>	<p>Read the label before use. Great attention when you scrub surfaces painted with oil paints before the 60s because it may contain lead. During the preparation of surfaces avoid the inhalation of dust. Use a face mask. Product Safety Data Sheet (MSDS) is freely available for the product. Store in a safe</p>

	<p>place away from children and pets. The container should be tightly closed during storage. Do not empty into drains. Leave left over to dry in the container.</p>
GENERAL INFORMATION	<p>The STYLE SEALER can be used on surfaces already painted with varnish stone solvent. The STYLE SEALER has very good resistance to abrasion, water, alcohol and common cleaners.</p> <p>The STYLE SEALER dries to form transparent crystal film on the substrate.</p> <p>After applying and 2 layers, allow 3-4 hours for light use at least 24 hours for normal use.</p> <p>If the product remains in a closed container, protected from extreme temperatures, has a shelf life of more than 2 years.</p> <p>Maximum application temperature: 30 oC.</p> <p>The information in particular the recommendations relating to the application and final use of products «STYLE BETON» given in good faith based on current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no guarantee can be given in respect of merchantability or fitness for a particular purpose and no liability of any legal relationship can be established against the company based here in labeling information, written</p>

recommendations, or other advice offered. Respect the rights of others is essential. Users must always refer to the most recent version of this.



STYLE BETON

NAVARINOU 8, KALOCHORI, THESSALONIKI, 57009

TEL. : 2310 - 920831, FAX : 2310 - 920832,

www.stylebeton.com , info@stylebeton.com