




STYLE BETON®

Deco Pebble

DESCRIPTION	<p>Style Beton® Deco Pebble is an exposed aggregate floor that furnish and personalize outside areas through a variety of colors and designs.</p> <p>Using small natural stones of different sizes we can obtain several architectonic and color effects respecting the ecological environment balance.</p> <p>Style Beton® Deco Pebble is a product based upon fibers, pigments, dispersants, products anti-efflorescence and additives, which, mixed with cement and gravel of different colors, shapes and dimensions, makes a mixture that it can be applied with a thickness from 2 to 4 cm upon both fresh or dry concrete.</p>
Colors Restrictions Packaging Storage	<p>Available in 4 colors.</p> <p>Do not apply the product in the likelihood of rain, the temperature of the substrate below 5 ° C and above 30 ° Celsius.</p> <p>25 kg</p> <p>At room temperature onto pallets. Protect from moisture.</p>
Application	<p><u>FIRST DAY-STEP 1:</u> We mix every sack of Decopebble (25kg) with 5kg cement, gray or white.</p> <p><u>FIRST DAY-STEP 2:</u> We apply on concrete sub-base the mix of Decopebble.</p> <p>a) We apply minimum 2 cm (31,5kg/m²) Decopebble (wet-on-wet) on fresh concrete surface, which we have left to absorb the water.</p> <p>b) We apply minimum 4 cm (63kg/m²) Decopebble on old concrete surface, on which we have applied earlier a coat of Polystyle.</p>

	<p><u>FIRST DAY-STEP 3:</u> We apply the mix.</p> <p><u>FIRST DAY-STEP 4:</u> We make the surface smooth and leave the mix to absorb the surface water.</p> <p><u>FIRST DAY-STEP 5:</u> We spread the surface with Style Lack and cover the surface with nylon.</p> <p><u>SECOND DAY-STEP 6:</u> We rinse the surface, using water pump and fresh water.</p> <p><u>SECOND DAY-STEP 7:</u> Decopebble Floor is ready and we can apply Style Sealer, when the surface is dry.</p>
CLEANING	The tools are recommended to be cleaned immediately after use with water.
HEALTH AND SAFETY	Read the label before use .During the preparation of surfaces avoid the inhalation of dust. Use a face mask and gloves. It contains toxic.
GENERAL INFORMATION	<p>Note that the technical application and the experience of work teams will affect the final aesthetic result of the floor.</p> <p>The information and in particular the recommendations relating to the application and final use of products «STYLE BETON®» given in good faith, based on current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual application conditions are such that no guarantee can be given in respect of merchantability or fitness for a particular purpose and no liability of any legal relationship can be established against the company based here in labeling information, written recommendations, or other advice offered. Respect the rights of others is essential. Users must always refer to the most recent version of this.</p> <div data-bbox="868 1671 995 1809" style="text-align: center;">  </div> <div data-bbox="619 1899 1246 1995" style="text-align: center;"> <p>STYLE BETON® Navarinou 8, Kalochori, Thessaloniki, Greece, 57009 TEL. : 0030 2310 - 920831, FAX : 0030 2310 - 920832, www.stylebeton.com , info@stylebeton.com</p> </div>